Title: Role of Calcium and Iron in SO₃ Formation in Coal-Fired Power Plants: Laboratory and Field Studies

Authors: Constance L. Senior

senior@psicorp.com Lawrence E.Bool III

Shin G.Kang

telephone: 978.689.0003

fax: 978.689.3232 Physical Sciences Inc.

20 New England Business Center

Andover, MA 01810

Stephen A. Johnson stevej47@worldnet.att.net telephone: 603.425.6765

ADA Environmental Solutions 30 Hickory Lane

Windham, NH 03087

Summary

Mineral matter in coal plays an important role in the emissions of sulfur dioxide and particulate matter. Iron oxide in ash can act as a catalyst for the oxidation of SO_2 to SO_3 , resulting in better performance of an electrostatic precipitator and thus lower particulate emissions. Calcium in ash can react with SO_2 (and SO_3) to give a lower level of sulfur emissions than predicted from analysis of the coal. Reaction of calcium in fly ash could also remove SO_3 from the flue gas. This latter effect could impact flue gas conditioning by addition of SO_3 , effectively neutralizing the conditioning. Physical Sciences Inc. (PSI) has carried out laboratory experiments and field testing to develop a better understanding of the fate of sulfur during coal combustion. The end result of this effort has been the development of a software package, Compliance AdvisorTM, which predicts the effect of coal composition on slagging, SO_2 emissions, and particulate emissions from coal-fired power plants.

Laboratory studies have determined the relevant temperature range for reaction of gaseous SO_2 with flyash as well as the temperature range for oxidation of SO_2 to SO_3 by iron-containing materials. These laboratory results have been validated by field testing at two full-scale boilers. Field testing has also revealed the importance of ash deposits in the convective pass in determining both the SO_2 and SO_3 concentrations in the flue gas.